


Shrink collar – TPSPM-PE

1. Product application

Shrink collars TPSPM-PE are a heat-shrinkable, tubular sleeves for joint sealing of heat-shrinkable and oversized casings. Products are dedicated to be used as an additional outside seal against moisture ingress at casing ends. Each product is equipped with adhesive (high strength visco-elastic sealant) and packed in protective foil.

2. Product diameters



Item number	Casing pipe external diameter [mm]	Min supplied diameter [mm]	Max recovered diameter [mm]	Product width [mm]	Packing pcs/box
850950651502	65-75	95	65	150	125
851150801502	90	115	80	150	90
851300901502	90-110	130	90	150	75
851551001502	110-125	155	100	150	60
851701101502	125-140	170	110	150	60
851901251502	140-160	190	125	150	60
852101351502	160-180	210	135	150	60
852251451502	180-200	225	145	150	60
852601651502	200-225	260	165	150	60
852601652252	200-225	260	165	225	60
852901851502	225-250	290	185	150	60
852901852252	225-250	290	185	225	60
853302101502	250-280	330	210	150	45
853302102252	250-280	330	210	225	30
853702351502	280-315	370	235	150	45
853702352252	280-315	370	235	225	30
853952501502	315-355	395	250	150	45
853952502252	315-355	395	250	225	30
854502852252	355-400	450	285	225	30
855053152252	400-450	505	315	225	20
855553502252	450-500	555	350	225	20
856253852252	500-560-710	625	385	225	14
857754802252	560-630-710	775	480	225	10
858655252252	710-800	865	525	225	10

Shrink collar – TPSM-PE

3. Storage

To ensure maximum performance, store the product in a dry, ventilated area. Keep products sealed in original boxes and avoid exposure to direct sunlight, rain, snow, dust or other adverse environmental elements. Avoid prolonged storage temperatures above 40°C or below -10°C. Unlimited shelf life.